



Fountain, Aerator, & Circulator Control Panels



C-25, 120V Single Phase Control Box for 120V Kasco Fountain, Aerator, and/or Circulator Models

C-85 & C-95, 240V, Single Phase Control Panel for 240V Kasco Fountain, Aerator, and/or Circulator Models



Power Control Panels

<u>Quick Facts</u>	<u>C-25</u>	<u>C-85</u>
<ul style="list-style-type: none"> ⇒ U.L. Listed per National Electric Code (NEC) Standards ⇒ Class A Human Rated GFCI ⇒ 24 Hour Built In Mechanical Timer, Each with 2 ON and 2 OFF Trippers ⇒ Built In Photo Cell for Optional Low Voltage Lighting Kits ⇒ 120V GFI Receptacle for Optional Lighting ⇒ NEMA Type 3R Weatherproof Enclosure ⇒ 2 Year Warranty ⇒ UPS Shippable ⇒ Made in the USA ⇒ Industrial Strength Design ⇒ Built In Mounting Fixtures 	<ul style="list-style-type: none"> ⇒ 120V, Single Phase ⇒ Plug & Go 120V Hook Up ⇒ 15 Amp Single Pole Class A Human Rated GFCI ⇒ 24 Hour Mechanical Timer with Two Each ON and OFF Trippers ⇒ Photo Cell for Optional Light Kit ⇒ UV Resistant NEMA Type 3R Weatherproof Plastic Enclosure with Two Cord Entry Bottom Openings ⇒ Wired 120V "UNIT" Outlet ⇒ Wired 120V "LIGHT" Outlet ⇒ Door Mounted Instructions ⇒ Lockable Enclosure 	<ul style="list-style-type: none"> ⇒ 240V, Single Phase ⇒ 20 Amp Double Pole Square D® Class A Human Rated GFCB ⇒ Built In Surge Protector ⇒ 24 Hour Mechanical Timer with Two Each ON and OFF Trippers ⇒ Photo Cell for Optional Light Kit ⇒ Relay, Single Pole 15 Amp Breaker, Photo Cell, and 120V GFI Receptacle Built In for Optional Light Kit ⇒ Requires 4 Wire Power (L1, L2, Ground, and Neutral) ⇒ Equipment May Be Plugged in to External Covered Outlet or Hardwired Into Panel ⇒ NEMA Type 3R Weatherproof Steel Coated Enclosure ⇒ Door Mounted Wiring Schematic ⇒ Lockable Enclosure
		<u>C-95</u>
		<ul style="list-style-type: none"> ⇒ 240V, Single Phase ⇒ 30 Amp Double Pole Square D® Class A Human Rated GFCB ⇒ Built In Surge Protector ⇒ 24 Hour Mechanical Timer with Two Each ON and OFF Trippers ⇒ Photo Cell for Optional Light Kit ⇒ Relay, Single Pole 15 Amp Breaker, Photo Cell, and 120V GFI Receptacle Built In for Optional Light Kit ⇒ Requires 4 Wire Power (L1, L2, Ground, and Neutral) ⇒ Equipment Must Be Hardwired Into Panel ⇒ NEMA Type 3R Weatherproof Steel Coated Enclosure ⇒ Door Mounted Wiring Schematic ⇒ Lockable Enclosure

Control Panel Specifications

Model #	Voltage/Phase/Hz	Breaker Size	Shipping Weight	Number of Boxes
C25	120/1/60	15 Amp	5 Lbs.	1
C85	240/1/60	20 Amp	18 Lbs.	1
C95	240/1/60	30 Amp	18 Lbs.	1

Kasco Marine, Inc.
800 Deere Rd.
Prescott, WI 54021

Ph: (715) 262-4488 * Fax: (715) 262-4487
www.KascoMarine.com * www.GotAlgae.com
Sales@KascoMarine.com

